



Key Specifications and benefits

- Flash Drive embedded Operating System
- Main CPU supporting packet rates up to 100,000 PPS (depending on application)
- 2 x 10/100/1000 Ethernet interfaces, with VLAN support
- Up to 80 serial ports supporting speeds to 2Mbps
- Optional second CPU operating in standby/ failover mode
- Hot swap WAN modules
- Up to four load sharing hot swap power supplies
- Auto synchronisation of configurations of systems in a cluster
- 10,000 concurrent connections
- Can be managed by SNMP, MegaWATCH or NMVT systems
- Ability to store up to 5 separate configurations
- Environmental module for monitoring temperature, voltage and fan fail

MegaPAC V-IX 7000 Product Overview



Scalability and Efficiency

The MegaPAC V-IX 7000 platform is a new generation of product, which is able to leverage high-end processors while protecting the skills our customers have in the operating system. Although we have introduced a user-friendly interface the essential strengths of our operating system are preserved. Large networks typically require complex configurations and as they expand become increasingly dependant on the ability to easily manage these while maintaining the flexibility of adequate processing power.

Performance

Although not the absolute measure in terms of ability, packet handling speed is a barrier which is invariably reached on any platform. Designing a system that provides the necessary excess capacity has driven our development to be able to launch this product with more than sufficient processing power to handle our customers' current requirements. As a high-end VPN termination platform the MegaPAC V-IX 7000 is able to handle in excess of 1000 protocol tunnels. Utilising modern architecture, the increased memory and thus increased availability of buffers means the number of network configurations handled, is dramatically increased. A further advantage is that these are achievable on a single platform. Our existing SNMP management platform is seamlessly available too, providing further protection of our customers' investment.

AEP

Ultra
ELECTRONICS

Redesigned Architecture

The redesigned architecture features a solid state flash drive. This replaces the original HDD with a 16-slot high speed cPCI BUS based on the PICMG 2.16 standard. All modules are hotswap with an option for a second standby/failover CPU for high availability and continuity of operations. Each CPU can be upgraded, configured and tested individually without impacting operations and then rolled out to the other CPU. Each MegaPAC V-IX 7000 chassis supports up to 80 serial ports at speeds of 2Mbps and dual Gigabit Ethernet interfaces.

Functional Specification

Serial Link Support	Standard: <ul style="list-style-type: none"> VadOS V-TES Frame relay NNI/UNI, LMI (ANSI & ITU) Switched and PVC TCP/IP PPP (RFC 1331), SLIP TPAD PAP/CHAP & MLP X.25 (1980 & 1984), X.32 OSI Transport (Class 0, 2, 3) V.25bis Async port up to 115.2Kbaud (X.3, X.28, X.29) HDLC transparent pass-through Bandwidth management Auto link back-up Link and Channel bonding 	TCP/IP	Standard: <ul style="list-style-type: none"> MAC bridging, IP routing OSPF, RIP, RIP2 NAT/PAT OSI TP4 GOSIP CLNS/CONS BootP Client DHCP client DHCP Server IP/UDP encapsulation with DiffServ Port/Address Filtering Metro Ethernet 802.1p 802.1q Ethernet trunk Optional: <ul style="list-style-type: none"> IPX routing, OSI ES-IS DLC local termination
Terminal Emulation	Standard: <ul style="list-style-type: none"> TCP Telnet (Client & Server) Transparent Telnet (RFC 1006) Optional: <ul style="list-style-type: none"> ICL 7561 Hitachi T560 IBM 3270 (inc.Kanji) Telnet (RFC 1646) 	Satellite Networking	Standard: <ul style="list-style-type: none"> VadOS V-TES SCPC, TDM/SCPC (Integral Support) Inmarsat BGAN/RBGAN) Asymmetrical & Symmetrical clocking Data Splitter/Combiner TCP Acceleration Serial VSAT Terrestrial Link Back up IP VSAT Terrestrial Link Back up
IBM Networking	Standard: <ul style="list-style-type: none"> SDLC QLLC Ethernet DLC 	Management Support	Standard: <ul style="list-style-type: none"> Local async console (RS232) Virtual port for remote access SNMP (MIBs: MIB2 & Enterprise) MegaWATCH (SNMP Management) Billing and Accounting Local/Remote configuration, upload, download, TFTP Remote software download, TFTP RADIUS Internal protocol Data scope Menu and Presentation Service Security (Password, address validation) Optional: <ul style="list-style-type: none"> IBM Netview
Bandwidth Optimisation	Standard: <ul style="list-style-type: none"> V-TES (AEP Proprietary) IP/UDP Header compression IP/UDP/RTP Header compression Voice-frame multiplexing 		



Ultra Electronics
 AEP
 Knaves Beech Business Centre
 Loudwater
 High Wycombe
 Buckinghamshire, HP10 9UT
 Main Switchboard: +44 (0)1628 642 600
 Email: info@ultra-aep.com
 www.ultra-aep.com
 www.ultra-electronics.com